

# Product Data Sheet

666-(2)-05/14



Makers of Fine Paint Since 1962

ISSUED: 10 May 2014

Page 1 of 2

## 666 Vinyl Primer

### USE



### THINNER/CLEAN



Spraying  
667 Vinyl  
Thinners

### APPLICATION



### RE-COAT



2 Hrs

### HAZARD



*666 Vinyl Primer (in older literature also known as Marine Systems or Forminex Anti Fouling Primer) is a single pack solvent based primer. It has excellent bleed stopping properties and provides superior adhesion to a wide range of substrates including: wood, steel, masonry and fibreglass. 666 Vinyl Primer may be used on surfaces that will remain immersed in water.*

**USES:** 666 Vinyl Primer has the following uses-

**PRIMER:** For use as a primer under most single-pack paints including enamel, acrylic, chlorinated rubber, vinyl coatings and anti-foulings.

**BARRIER COAT:** As a barrier coat over most anti-foulings,

**FINISHING COAT:** 666 Vinyl Primer can also be used as a self priming finishing coat when 2 or 3 coats are applied.

**COLOUR:** Silver grey. Has the appearance of new galvanising.

**SURFACE PREPARATION:** Ensure surface is clean & dry, & that all loose dirt, rust, oil, grease, flaking paint etc. are completely removed. Hard glossy surfaces should be well abraded to ensure good adhesion.

**APPLICATION:** By brush, roller or spray. 666 Vinyl Primer can be Spray applied but this involves particular hazards and should only be undertaken by professionals experienced in this field.

**WHEN TO PAINT:** Ideal application temperature 15 to 30°C Avoid painting in direct sunlight as this will cause paint to dry too quickly. Do not paint if temperature is likely to drop below 10°C during curing period.

**DRYING / RE-COATING:** Touch dry in 10 mins at 25°C. Recoat 2 hours (depending on temperature & atmospheric moisture).

**THINNING:** Product is ready for use when brushing or rolling. If spraying use only 667 Vinyl Thinners.

**CLEAN UP:** Clean equipment with 667 Vinyl Thinners. Do not clean hands with solvents, use suitable hand cleaner.

**COVERAGE:** 5 to 8 m<sup>2</sup>/litre depending on porosity of surface.

TOPLINE PAINT PTY LTD

33 ALDERSHOT ROAD, LONSDALE, SOUTH AUSTRALIA 5160.

Telephone: (08) 8384 1188

Fax: (08) 8326 1824

E-mail: admin@toplinepaint.com.au

Customers need to appreciate that as Topline Paint cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.





## 666 Vinyl Primer

### PRECAUTIONS:

*The following information is a general guide only. Industrial users (ie where the product is being used in the workplace) are legally required to have available a Material Safety Data Sheet on this product. If you are unsure if you have an MSDS on this product please contact Topline Paint and one will be provided.*

**Safety Directions:** **KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.** Breathing the vapour is harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use. Eliminate any source of ignition (open fires, pilot lights, furnaces, spark producing switches etc.) as this product is flammable. **DO NOT SMOKE.** Take precautionary measures against static discharges. Used clean up rags may spontaneously ignite. To avoid ignition immerse in water or store in a sealable glass container.

**First Aid Instructions:** If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

**Leaks, Spills and Disposal:** To prevent ignition of fumes product shut off all ignition sources. Contain or shut off leak if safe to do so. For large leaks or spills of volatile, flammable product, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). In the case of flammable product spillage, use spark free implements to place rags or absorbed material into a solvent resistant container. Cover with water for 24 hours before disposal. DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

**Fire:** Use foam and breathing apparatus. Avoid breathing products of combustion.

**Hazard:** The coloured square at the top of page 1 is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes